

<p><b>PRIMARY ENCLOSURE-VENTILATION</b></p>	<p>A transport primary enclosure, such as a compartment, transport cage, carton, or crate, used to transport an animal in commerce must be adequately ventilated.          [3.14, 3.36, 3.61, 3.87, 3.113, 3.137]</p>																			
<p><b>Criteria</b></p>	<p><b>For transport enclosures permanently affixed</b> to the primary conveyance with the front opening as the only source of ventilation, the enclosure ventilation area must:</p> <ul style="list-style-type: none"> <li>• be positioned to prevent blockage of front opening</li> <li>• open directly to an unobstructed aisle way or passageway inside the conveyance</li> <li>• be at least 90% of the total surface area</li> <li>• be covered with bars, wire mesh, or smooth expanded metal having air space</li> </ul>																			
<p><b>Species Specific</b></p>	<p><b>Dogs &amp; Cats</b>  <b>Transport enclosures that are removable</b> from the primary conveyance, such as crates, cartons, or cages, must have walls with ventilation openings that meet the following requirements: [3.14(c)]</p> <table border="1" data-bbox="537 1087 1351 1577"> <thead> <tr> <th data-bbox="537 1087 716 1220">Number of ventilated walls</th> <th data-bbox="716 1087 943 1220">Position of the walls</th> <th data-bbox="943 1087 1351 1220">Required ventilation area</th> </tr> </thead> <tbody> <tr> <td data-bbox="537 1220 716 1283">1</td> <td data-bbox="716 1220 943 1283">front</td> <td data-bbox="943 1220 1351 1283">90%</td> </tr> <tr> <td data-bbox="537 1283 716 1346">2</td> <td data-bbox="716 1283 943 1346">opposing walls</td> <td data-bbox="943 1283 1351 1346">16% of each wall</td> </tr> <tr> <td data-bbox="537 1346 716 1520" rowspan="2">3</td> <td data-bbox="716 1346 943 1451">2 opposing walls</td> <td data-bbox="943 1346 1351 1451">8% of total surface area of the two opposing walls</td> </tr> <tr> <td data-bbox="716 1451 943 1520">3<sup>rd</sup> wall</td> <td data-bbox="943 1451 1351 1520">50% of the 3<sup>rd</sup> wall</td> </tr> <tr> <td data-bbox="537 1520 716 1577">4</td> <td data-bbox="716 1520 943 1577">4 opposing</td> <td data-bbox="943 1520 1351 1577">8% of each wall</td> </tr> </tbody> </table> <p>The ventilated surface area must:</p> <ul style="list-style-type: none"> <li>• be 14% of the total combined surface area of all the walls for the whole enclosure, and [3.14(c)(1)]</li> </ul>			Number of ventilated walls	Position of the walls	Required ventilation area	1	front	90%	2	opposing walls	16% of each wall	3	2 opposing walls	8% of total surface area of the two opposing walls	3 <sup>rd</sup> wall	50% of the 3 <sup>rd</sup> wall	4	4 opposing	8% of each wall
Number of ventilated walls	Position of the walls	Required ventilation area																		
1	front	90%																		
2	opposing walls	16% of each wall																		
3	2 opposing walls	8% of total surface area of the two opposing walls																		
	3 <sup>rd</sup> wall	50% of the 3 <sup>rd</sup> wall																		
4	4 opposing	8% of each wall																		

- have at least **a** of the total ventilation area located on the upper ½ of the enclosure [3.14(c)(1)(iv)]

Each wall with a ventilation opening must have a projecting rim to:

- prevent obstruction of openings
- provide a minimum of 0.75" air circulation space between the enclosure and any wall or object

**Guinea Pigs & Hamsters**

**Transport enclosures that are removable** from the primary conveyance, such as crates, cartons, or cages, must have walls with ventilation openings that meet the following requirements: [3.36]

Number of ventilated walls	Position of the walls	Required ventilation area
1	front	90%
2	opposing walls	16% of each wall
4	4 opposing	8% of each wall

The ventilated surface area must have [3.36(a)(5)]

- at least **a** of the total ventilation area located on the **upper** ½ of the enclosure, and
- at least **a** of the total ventilation area located on the **lower** ½ of the enclosure

Each wall with a ventilation opening must have a projecting rim to [3.36(a)(6)]

- prevent obstruction of openings
- provide a minimum of 0.75" air circulation space between the enclosure and any wall or object

**Rabbits**

**Transport enclosures that are removable** from the primary conveyance, such as crates, cartons, or cages, must have walls with ventilation openings that meet the following requirements: [3.61]

Number of ventilated walls	Position of the walls	Required ventilation area
1	front	90%
2	opposing walls	16% of each wall
4	4 opposing	8% of each wall

The ventilated surface area must have: [3.61(a)(4)]

- at least **a** of the total ventilation area located on the **upper** ½ of the enclosure, and
- at least **a** of the total ventilation area located on the **lower** ½ of the enclosure

Each wall with a ventilation opening must have a projecting rim to: [3.61(a)(5)]

- prevent obstruction of openings
- provide a minimum of 0.75" air circulation space between the enclosure and any wall or object

**Nonhuman Primates**

**Transport enclosures that are removable** from the primary conveyance, such as crates, cartons, or cages, must have walls with ventilation openings that meet the following requirements: [3.87(c)]

Number of ventilated walls	Position of the walls	Required ventilation area	Location of openings
1	front	90%	
2	opposing walls	16% of each wall	above midline of each wall
4	4 opposing	8% of each wall	above midline of each wall

Each wall with a ventilation opening must have a projecting rim to [3.87(c)(2)]

- prevent obstruction of openings
- provide a minimum of 0.75" air circulation space between the enclosure and any wall or object

**Marine Mammals**

RESERVED-Pending approval of negotiated rules.

**Other Animals**

**Transport enclosures that are removable** from the primary conveyance, such as crates, cartons, or cages, must have walls with ventilation openings that meet the following requirements:

[3.137(a)(4), 3.137(g)]

Number of ventilated walls	Position of the walls	Required ventilation area
1	front	90%
2	opposing walls	16% of each wall
4	4 opposing	8% of each wall

The ventilation area must: [3.137(a)(4)]

- have at least **a** of the total ventilation area located on the **upper** ½ of the enclosure, and
- have at least **a** of the total ventilation area located on the **lower** ½ of the enclosure

Each wall with a ventilation opening must have a projecting rim to: [3.137(a)(5)]

- prevent obstruction of openings
- provide a minimum of 0.75" air circulation space between the enclosure and any wall or object